



**DIMS FOR COMPACT DRIVE SYSTEM - PANELS ≤ 26.5"**

Finished Ceiling "A"	Beam Height "B"	Acoustic Barrier "C"	Pocket Depth "D"	Pocket Width "E"	Panel Height "F"	Number of Panels High	Wall Thickness	Max Panel Length		
								Classic	Classic NR	Classic Elite
7'-0"	9'-2 1/4"	8'-2 1/2"	14 1/2"	56 3/4"	23 1/2"	4 Panels High	11 3/4"	12'	12'	12'
7'-6"	9'-8 1/4"	8'-8 1/2"	14 1/2"	59 3/4"	25"					
8'-0"	10'-2 1/4"	9'-2 1/2"	14 1/2"	62 3/4"	26 1/2"					
8'-1"	10'-8 1/2"	9'-8"	20"	53 1/4"	22"	5 Panels High	11 3/4"	12'	12'	12'
8'-6"	11'-1 1/2"	10'-1"	20"	55 1/4"	23"					
9'-0"	11'-7 3/4"	10'-7 1/4"	20 1/4"	59 1/4"	24 1/4"					
9'-6"	12'-2"	11'-1 1/2"	20 1/2"	61 3/4"	25 1/2"					
10'-0"	12'-7"	11'-6 1/2"	19 1/2"	63 3/4"	26 1/2"					
10'-1"	12'-9"	11'-9 1/4"	20 1/4"	53 1/2"	22 5/8"	6 Panels High	11 3/4"	12'	12'	12'
10'-6"	13'-2 1/4"	12'-2 1/2"	20 1/2"	56 3/4"	23 1/2"					
11'-0"	13'-8 1/4"	12'-8 1/2"	20 1/2"	58 3/4"	24 1/2"					
11'-6"	14'-2 1/4"	13'-2 1/2"	20 1/2"	60 3/4"	25 1/2"					
12'-0"	14'-8 1/4"	13'-8 1/2"	20 1/2"	62 3/4"	26 1/2"					
12'-1"	15'-2 1/4"	14'-1 3/4"	25 3/4"	57 1/4"	23 1/4"	7 Panels High	11 3/4"	12'	12'	12'
12'-6"	15'-7 1/2"	14'-7"	26"	58 3/4"	24"					
13'-0"	16'-0 3/4"	15'-0 1/4"	25 1/4"	60 1/4"	24 3/4"					
13'-6"	16'-7 3/4"	15'-7 1/4"	26 1/4"	62 1/4"	25 3/4"					
14'-0"	17'-1"	16'-0 1/2"	25 1/2"	63 3/4"	26 1/2"					
14'-1"	17'-2 1/4"	16'-2 1/2"	25 1/2"	56 3/4"	23 1/2"	8 Panels High	11 3/4"	12'	12'	12'
14'-6"	17'-7 1/4"	16'-7 1/2"	25 1/2"	58"	24 1/8"					
15'-0"	18'-1 1/4"	17'-1 1/2"	25 1/2"	59 1/2"	24 7/8"					
15'-6"	18'-7 1/4"	17'-7 1/2"	25 1/2"	61"	25 5/8"					
16'-0"	19'-1 1/4"	18'-1 1/2"	25 1/2"	62 1/2"	26 3/8"					
16'-1"	19'-2 1/4"	18'-2 1/2"	25 1/2"	62 3/4"	26 1/2"					
16'-2"	20'-1 3/4"	18'-8 1/2"	31 1/2"	58 3/4"	24"	9 Panels High	11 3/4"	12'	12'	12'
16'-6"	20'-6 1/4"	19'-1"	32"	59 3/4"	24 1/2"					
17'-0"	21'-1"	19'-7 3/4"	32 3/4"	61 1/4"	25 1/4"					
17'-6"	21'-7 3/4"	20'-2 1/2"	33 1/2"	62 3/4"	26"					
18'-0"	22'-0 1/4"	20'-7"	32"	63 3/4"	26 1/2"					
18'-1"	22'-0 3/4"	20'-9 1/4"	32 1/4"	59"	24 1/8"	10 Panels High	11 3/4"	12'	12'	10'
18'-6"	22'-5 3/4"	21'-2 1/4"	32 1/4"	60"	24 5/8"					
19'-0"	23'-0"	21'-8 1/2"	32 1/2"	61 1/4"	25 1/4"					
19'-6"	23'-6 1/4"	22'-2 3/4"	32 3/4"	62 1/2"	25 7/8"					
20'-0"	24'-0 1/2"	22'-9"	33"	63 3/4"	26 1/2"					
20'-1"	24'-8 1/4"	23'-3"	39"	59 3/4"	24 1/2"	11 Panels High	11 3/4"	12'	12'	8'
20'-6"	24'-11"	23'-5 3/4"	36 3/4"	60 1/4"	24 3/4"					
21'-0"	25'-7 1/4"	24'-2"	39"	61 3/4"	25 1/2"					
21'-6"	26'-0 3/4"	24'-7 1/2"	38 1/2"	62 3/4"	26"					
22'-0"	26'-6 1/4"	25'-1"	38"	63 3/4"	26 1/2"					
22'- 1"	26'-5 3/4"	25'-2 1/4"	37 1/4"	59 5/8"	24 7/16"	12 Panels High	11 3/4"	12'	10'	8'
22'- 6"	26'-11"	25'-7 1/2"	37 1/2"	60 1/2"	24 7/8"					
23'- 0"	27'-5"	26'-1 1/2"	37 1/2"	61 1/2"	25 3/8"					
23'- 6"	27'-11"	26'-7 1/2"	37 1/2"	62 1/2"	25 7/8"					
24'- 0"	28'-5"	27'-1 1/2"	37 1/2"	63 1/2"	26 3/8"					
24'- 2"	28'-6 1/2"	27'-3"	37"	63 3/4"	26 1/2"					

**\* Beam Heights indicated may vary with wall size and motor size.**

This table is not for construction purposes. Refer to shop drawings for final build to dimensions.



**DIMS FOR COMPACT DRIVE SYSTEM - PANELS ≤ 26.5"**

Finished Ceiling "A"	Beam Height "B"	Acoustic Barrier "C"	Pocket Depth "D"	Pocket Width "E"	Panel Height "F"	Number of Panels High	Wall Thickness	Max Panel Length		
								Classic	Classic NR	Classic Elite
24'-3"	29'-2 1/2"	27'-8 1/4"	42 1/4"	61 1/4"	24 3/4"	13 Panels High	11 3/4"	10'	10'	8'
24'-6"	29'-5 3/4"	27'-11 1/2"	42 1/2"	61 3/4"	25"					
25'-0"	30'-0 1/4"	28'-6"	43"	62 3/4"	25 1/2"					
25'-6"	30'-6 3/4"	29'-0 1/2"	43 1/2"	63 3/4"	26"					
26'-0"	31'-1 1/4"	29'-7"	44"	64 3/4"	26 1/2"					
26'-1"	31'-0 3/4"	29'-8 1/2"	43 1/2"	61 1/4"	24 3/4"	14 Panels High	11 3/4"	10'	8'	8'
26'-6"	31'-6"	30'-1 3/4"	43 3/4"	62"	25 1/8"					
27'-0"	31'-11 1/4"	30'-7"	43"	62 3/4"	25 1/2"					
27'-6"	32'-6 1/4"	31'-2"	44"	63 3/4"	26"					
28'-0"	32'-11 1/2"	31'-7 1/4"	43 1/4"	64 1/2"	26 3/8"					
28'-2"	33'-1 1/4"	31'-9"	43"	64 3/4"	26 1/2"					
28'-3"	33'-8 3/4"	32'-2 1/2"	48 1/2"	61 3/4"	25"	15 Panels High	11 3/4"	10'	8'	N/A
28'-6"	34'-0"	32'-6 1/4"	49 1/4"	62 1/4"	25 1/4"					
29'-0"	34'-7 1/2"	33'-1 3/4"	50 3/4"	63 1/4"	25 3/4"					
29'-6"	34'-11 1/4"	33'-5 1/2"	48 1/2"	63 3/4"	26"					
30'-0"	35'-6 3/4"	34'-1"	50"	64 3/4"	26 1/2"					
30'-1"	35'-9"	34'-2"	49"	61 5/8"	24 15/16"	16 Panels High	11 3/4"	8'	8'	N/A
30'-6"	36'-2"	34'-7"	49"	62 1/4"	25 1/4"					
31'-0"	36'-8"	35'-1"	49"	63"	25 5/8"					
31'-6"	37'-2"	35'-7"	49"	63 3/4"	26"					
32'-0"	37'-8"	36'-1"	49"	64 1/2"	26 3/8"					
32'-2"	37'-10"	36'-3"	49"	64 3/4"	26 1/2"					
32'-3"	38'-5 1/2"	36'-9 3/4"	55 3/4"	62 1/4"	25 1/4"	17 Panels High	11 3/4"	8'	8'	N/A
32'-6"	38'-9 3/4"	37'-2"	57"	62 3/4"	25 1/2"					
33'-0"	39'-2"	37'-6 1/4"	55 1/4"	63 1/4"	25 3/4"					
33'-6"	39'-6 1/4"	37'-10 1/2"	53 1/2"	63 3/4"	26"					
34'-0"	40'-2 3/4"	38'-7"	56"	64 3/4"	26 1/2"					
34'-2"	40'-2 3/4"	38'-7"	54"	64 3/4"	26 1/2"					
34'-3"	40'-5 1/2"	38'-8 1/4"	53 1/4"	62"	25 1/8"	18 Panels High	11 3/4"	8'	N/A	N/A
34'-6"	40'-10"	39'-0 3/4"	54 3/4"	62 1/2"	25 3/8"					
35'-0"	41'-4 3/4"	39'-7 1/2"	55 1/2"	63 1/4"	25 3/4"					
35'-6"	41'-9 1/4"	40'-0"	54"	63 3/4"	26"					
36'-0"	42'-4"	40'-6 3/4"	54 3/4"	64 1/2"	26 3/8"					

**\* Beam Heights indicated may vary with wall size and motor size.**

This table is not for construction purposes. Refer to shop drawings for final build to dimensions.